Profiglass G 522

Ready-to-use glass cleaner





Area of application

- Interior glazing and surfaces, mirrors, frames, plastic and car windows

Product properties

- Dries quickly and streak-free
- Good cleaning effect, especially for greasy residues
- Leaves a radiant gloss
- Can be used selectively
- Meets the requirements within the framework of an HACCP concept

Application and dosage

- Spray on a suitable cleaning cloth and clean the surfaces.
- Consumption: 4 - 8 ml / per m²



undi-
luted

Note

- Check for material compatibility on a hidden area before use.
- Conditionally suitable on acrylic glass (PMMA).
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- **Safety:** Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at www.buzil.com.
- **Storage:** Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- **Environmental:** Feed residual emptied containers to the dual system. For detailed information see environmental information.

Further information

- **Product colour:** light blue
- Ingredients according to the EU Detergents Regulation (Det-VO*)**:** AQUA, ALCOHOL, BUTOXYPROPANOL, MEK, COLORANT, PARFUM, CAPRYL GLUCOSIDE, LAURYL GLUCOSIDE, PEG-40 HYDROGENATED CASTOR OIL, TRIDECETH-9
- **GISBAU code:** GGL 05
- **UFI code:** UA50-J0M6-P00X-UW7D

Sales units

- G522-0010RA: 1 x 10 l canister
- G522-0600RA: 12 x 600 ml bottle
- G522-0001RA: 12 x 1 l bottle

pH 7,5

0 2 4 6 8 10 12 14

* A database of correspondences between INCI names, European Pharmacopoeia names and CAS numbers is provided on the European Commission Pharmacos website: https://ec.europa.eu/growth/tools-databases/cosing/

Remark: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

Date 25.01.2024

BUZIL-WERK Wagner GmbH & Co. KG • Fraunhoferstraße 17 • D-87700 Memmingen • www.buzil.com