

Corridor® Black S 739

Black dispersion







Area of application

- For water-resistant, absorbent and coatable (also with residual moisture) and thoroughly cleaned floor coverings such as stone, asphalt, cement and concrete screed, bitumen, linoleum
- Particularly suitable for industrial flooring for recoloring and care of heavily used floor surfaces, e.g. B. in exhibition halls and workshops

Product properties

- Durable, black colouring polymer dispersion
- Forms a resistant protective film
- Very good filling power and good flow properties
- High coverage for an excellent look
- Free of metal salt
- Slip-resistant according to DIN 51131
- Sealing by final application matt, glossy, high-gloss possible

Application and dosage

- Apply a thin layer on thoroughly cleaned, neutralized and dry floor covering with a mop or a scrubber.
- Let it dry thoroughly and repeat the process.
- Perform the last application with a colourless coating, S 734, S 737, S 741.
- For sealing, choose between Corridor® Glorin S 734 for glossy, Corridor® Matt S 737 for matte or Corridor® Jewel S 741 for high-gloss.
- Consumption: 25 35 ml / per m2 / per order



luted

Note

- Protect from frost.
- Before processing, turn off heat sources (underfloor heating, heating, hot supply air).
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- Safety: Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at www.buzil.com.
- Storage: Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- Environmental: Feed residual emptied containers to the dual system. For detailed information see environmental information.

Further information

Product colour: blackGISBAU code: GE 10

• UFI code: 3YR0-D0DC-500A-DYPD

• For professional use only.

Sales units

■ S739-0010RA: 1 x 10 l canister



Remark: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

